



Art.-No.: ED-073602-NW
LED recessed downlight "CANTONE", round, 68x49mm,
7W, 480lm, 4000K, CRI >80, IP20

LED recessed downlights, Cantone series. Four different covers in white, chrome, chrome matt and brushed metal, available in a round/square version. Operating unit can be dimmed (TRIAC/DALI dimmer), external. Version with CASAMBI® Bluetooth control available.



TECHNICAL DATA

Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Power Factor	0.85
System power	8.1 W
DC Ready	Yes
Connection cross section	1.5 mm ²
Dimming	TRIAC, DALI
Electrical version	with external operating device, dimmable
CASAMBI Ready	Yes
Photometrical data	
Light source	LED
Colour temperature	4,000 K
Rated luminous flux	480 lm
Light colour	840
Colour rendering index (CRI)	> 80
Beam angle	38 °
Lifetime (h, at 25°C)	50,000 h, L70
Acceptance tests	
Certifications	CE
Protection class	II
Ingress protection (IP) rating	IP 20
Ambient temperature	-20 to +45 C°
Storage temperature	-25 to +50 C°



Physical data	
Mounting method	recessed ceiling mounted, recessed wall mounted
Housing material	Aluminium
Housing colour	white
Length (L)	92 mm
Width (B)	92 mm
Height (H)	50 mm
Ceiling Cut-out \varnothing	68 mm
Recess height	50 mm
Product weight	0.18 kg
Weight incl. Packaging	0.28 kg
Packaging Length (L)	130 mm
Packaging Width (B)	100 mm
Packaging Height (H)	75 mm