



**Art.-No.: YWDRO-RAWS-2601-DS**  
**LED luminaire "RONDA", wall / ceiling surface mounting,**  
**round, 395x108mm, 26W, 1900lm, 3000K, CRI >80, IP20,**  
**silver, switchable**

LED ceiling- and wall-mounted luminaire, Ronda series. Housing made from aluminium, silver or white, IP20. Diffuser made from plastic (PMMA), opal, UV-stabilised. Operating unit can be switched, installed. Version with Casambi Bluetooth control available.



## TECHNICAL DATA


Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Power Factor	0.9
System power	26 W
Inrush current	10 A
Luminaires on B10A fuse	40 Stk.
Luminaires on B16A fuse	64 Stk.
DC Ready	Yes
Connection cross section	1.5 mm <sup>2</sup>
Electrical version	with internal operating device, switchable
CASAMBI Ready	Yes
Photometrical data	
Light source	LED
Colour temperature	3,000 K
Rated luminous flux	1,900 lm
Light colour	830
Colour rendering index (CRI)	> 80
Beam angle	120 °
UGR	24.5
Lifetime (h, at 25°C)	50,000 h, L80



Acceptance tests	
Certifications	CE, ROHS
Protection class	II
Ingress protection (IP) rating	IP 20
Impact resistance	IK 02
Ambient temperature	-20 to +40 C°
Storage temperature	-20 to +45 C°
Physical data	
Mounting method	ceiling mounted, wall mounted
Housing material	Aluminium
Housing colour	silver
Height (H)	108 mm
Diameter ø	395 mm
Product weight	1.4 kg
Weight incl. Packaging	1.5 kg
Packaging Length (L)	440 mm
Packaging Width (B)	440 mm
Packaging Height (H)	120 mm



**LIGHT DISTRIBUTION**



cd/klm

$\eta = 100\%$

— C0 - C180    — C90 - C270